

ACTIVE TOOLING


For General Applications Cross Cutting / Plywood

一般木材〈ヨコ挽き用〉／合板〈切断用〉



SPECIFICATION 02

blade type : **A**



blade type : **C**



一般木材



合板



ヨコ挽き・切断

外径 (D)	刃厚 (T1)	台厚 (T2)	内径 (d)	刃数 (Z)	刃型 blade type
150	3.0	2.2	25.4	40	A
205	1.8	1.2	25.4	60	A
	2.4	1.6	25.4	60	A
	2.8	2.0	25.4	60	A
	3.0	2.2	25.4	60	A
255	1.8	1.2	25.4	80	A
	2.4	1.6	25.4	80	A
	2.8	2.0	25.4	80	A
	3.0	2.2	25.4	80	A
	1.8	1.2	25.4	100	A
	2.4	1.6	25.4	100	A
	2.8	2.0	25.4	100	A
305	3.0	2.2	25.4	100	A
	2.8	2.0	25.4	80	A
	3.0	2.2	25.4	100	A
	1.8	1.2	25.4	100	A
	2.4	1.6	25.4	100	A
	2.8	2.0	25.4	100	A
	3.0	2.2	25.4	100	A
355	1.8	1.2	25.4	120	A
	2.4	1.6	25.4	120	A
	2.8	2.0	25.4	120	A
	3.0	2.2	25.4	120	A
	3.0	2.2	25.4	80	A
	3.0	2.2	25.4	100	A
	3.0	2.2	25.4	120	A
405	3.2	2.4	25.4	80	A・C
	3.2	2.4	25.4	100	A・C
	3.2	2.4	25.4	120	A・C
455	3.2	2.4	25.4	80	A・C
	3.2	2.4	25.4	100	A・C
	3.2	2.4	25.4	120	A・C
510	3.2	2.4	25.4	80	A・C
	3.2	2.4	25.4	100	A・C
	3.2	2.4	25.4	120	A・C

有限 浜松チップソー工業所
会社

静岡県浜松市南区四本松町326-4
TEL 053-426-2824 FAX 053-425-5518 E-mail : act@h-tipsaw.co.jp

<http://www.h-tipsaw.co.jp>

※一般的な切断に使用できる標準品です。