

# ACTIVE TOOLING

For General Applications / Ripping

一般木材〈タテ挽き用〉



## SPECIFICATION 03

blade type : **BC**



blade type : **C**



blade type : **A**



blade type : **BA**



一般木材



スチロール



タテ挽き

※発泡ウレタン、スチロールの切断にも対応できます。

外径 (D)	刃厚 (T1)	台厚 (T2)	内径 (d)	刃数 (Z)	刃型 blade type
205	1.2	0.8	25.4	40	BC
	2.0	1.4	25.4	40	BC
	2.4	1.6	25.4	40	BC
	3.0	2.0	25.4	40	BC
	1.2	0.8	25.4	60	BC
	2.0	1.4	25.4	60	BC
230	2.4	1.6	25.4	60	BC
	3.0	2.0	25.4	60	BC
	1.3	0.9	25.4	40	BC
255	1.8	1.2	25.4	40	BC
	1.2	0.8	25.4	40	BC
305	2.0	1.4	25.4	40	BC
	2.4	1.6	25.4	40	BC
	3.0	2.0	25.4	40	BC
	1.2	0.8	25.4	60	BC
	2.0	1.4	25.4	60	BC
	2.4	1.6	25.4	60	BC
	3.0	2.0	25.4	60	BC
	1.6	1.1	25.4	40	BC
	2.0	1.4	25.4	40	BC
	2.4	1.6	25.4	40	BC
355	3.0	2.0	25.4	40	BC・C
	3.0	2.0	38.1	40	BC
	1.6	1.1	25.4	60	BC
	2.0	1.4	25.4	60	BC
	2.4	1.6	25.4	60	BC
	3.0	2.0	25.4	60	BC・C
	3.0	2.0	25.4	60	A・BA
	2.6	1.8	25.4	40	BC
	3.0	2.0	25.4	60	A・BA
	3.2	2.2	25.4	40	BC・C
405	3.4	2.4	38.1	30	BC
	2.6	1.8	25.4	60	BC
	3.2	2.2	25.4	60	BC・C
430	3.2	2.2	25.4	40	BC・C
	2.6	1.8	25.4	60	BC
	3.0	2.0	25.4	60	A・BA
455	3.2	2.2	25.4	60	BC・C
	3.2	2.2	25.4	60	BC・C

有限 浜松チップソー工業所

静岡県浜松市南区四本松町326-4  
TEL 053-426-2824 FAX 053-425-5518 E-mail : act@h-tipsaw.co.jp

<http://www.h-tipsaw.co.jp>

※パーチ・MDFの厚物、塩ビ・アクリルの厚物にも対応できます。  
※発泡ウレタン、発泡スチロールの切断にも対応できます。